

Home & Business Monitoring Kit

7" LCD Monitor & PNP-51 Security Camera



Mount camera & LCD to walls or ceilings

Flexible mounting options with all accessories included

LCD image flip option

Mount lcd monitor upside down or side ways & flip the image around the right way

Auto turn on/off LCD monitor

Set time to automatically turn the monitor on & off

Add a second camera

Automatically switch camera views at 4 to 8 second intervals

Do it yourself

See what's happening in high resolution color

Compact size

Discreet, small footprint & stylish finish

400

high video quality
1/3" CMOS 400 TV lines



16ft 5m
night vision



dual viewing mode
day(colour)/night(B&W)



discreet indoor use



built-in micorphone
hear audio



BNC cable
60ft 18m

Home & Business Monitoring Kit

7" LCD Monitor & PNP-51 Security Camera



Specifications

Video

Image Sensor	1/3" CMOS
Video Quality	400 TV Lines
Number of Effective Pixels	NTSC: 510 x 492 / PAL: 628 x 582
Minimum Illumination	0 Lux (IR on)
Day/Night Mode	colour during day / switches to B&W at night
White Balance	Automatic
Signal / Noise Ratio	> 50dB
Electronic Shutter	1/60 - 1/15,000 NTSC / 1/50 - 1/15,000 PAL
Gain Control	Automatic
Backlight Compensation	Yes
Lens	4mm
Viewing Angle	90 degrees

Audio

Microphone	Yes
Audio Range	Up to 3ft / 1m

Night Vision

Night Vision Distance	Up to 16ft / 5m
Number of Infra-Red LEDs	8
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000 hours

General

Indoor / Outdoor	Indoor
Operating Power	DC 12V
Operating Temperature	32°F ~ 113°F / 0°C ~ 45°C
Body Construction	Heavy Duty Plastic
Dimensions - Camera & Stand	4.25" x 2.75" x 1.75" / 108mm x 69mm x 44mm
Weight - Camera & Stand	4.23oz / 125g
Cable Length	60ft / 18m RCA

LCD

Display

Screen Size	7 Inches
Screen	TFT
LCD Profile Ratio	Ratio 16:9
Display Resolution	1440(H) x 234(V)
Contrast	300:1

Brightness 300cd/m2
 Reponse Time (ms) R:15/F:20
 Viewing Angle U:40/D:60 L/R:60
 Video Input 1VP-P 75 Ohm

Audio

Audio Input 1.5VP-P Stereo (left and right)
 Audio Output Build-in louder speaker (0.3w*2)

General

Power Supply 12V DC
 Connecting Terminal AV input jack x 2 external power supply input jack. English, Russian, German, French, Spanish, Portuguese, Italian and Dutch changeable
 OSD menu Yes
 Remote Control Yes
 Battery Qty & Type 2 x AAA
 Operation Temperature -10°C ~ 50°C / 14°F ~ 122°F
 Power Consumption approx. 10W

Package Contents

- PNP-51™ Camera
- 7" LCD Monitor & Accessories
- RCA to RCA Cable 3ft / 1m
- BNC Cables 60ft / 18m
- Power Adapters
- Remote Control
- Mounting Screws & Plugs
- Operating Instructions
- Theft Deterrent Stickers x 4

